



A Subsidiary of Garland Industries

# FasTape SRA-W

## DESCRIPTION

Low Density Polyethylene Film Tape - 9.0 mil - Synthetic Rubber Based Adhesive remains permanently tacky and bonds well to most surfaces over a wide range of temperatures; excellent low temperature bond. Tough polyethylene backing offers good abrasion and tear resistance. Highly conformable, waterproof and resistant to chemical deterioration.

## APPLICATIONS

Ideal for polyethylene splicing; patching/repairing poly sheeting used in boating and RV industry; surface protection & electroplate masking; wire identification; packaging; etc. Works well in most applications where a low thread count polyethylene coated cloth tape is being used.

## TECHNICAL DATA

| Properties                  | Value                        |
|-----------------------------|------------------------------|
| Total Thickness             | 9.0 mil (0.229 mm)           |
| Tensile Strength            | 22 lbs/inch width            |
| Elongation                  | 100%                         |
| Adhesion to Steel           | 60 oz/inch                   |
| Adhesion to Backing         | 35 oz/inch                   |
| Moisture Vapor Transmission | 0.4 grams/100 sq. in/24 hrs. |
| Color                       | White                        |
| Format                      | 4" x 60 yd                   |
| Core                        | 3"                           |

The information and recommendations discussed in this publication are believed to be correct. The ASTM testing is conducted by an independent accredited laboratory. No statement should be construed as a recommendation for any use, which would violate any patent rights. This document is not a guarantee of a warranty, if approved by GMX, Inc., a performance warranty may be granted.



**GMX, Inc.**  
3014 Chamber Dr.  
Monroe, NC 28110  
Toll Free: 866-228-7743  
[www.gmxco.com](http://www.gmxco.com)