



A Subsidiary of Garland Industries

BoneDry™ TG

DESCRIPTION

BoneDry™ TG is a commercial grade trowelable waterproofing mastic based on polymer modified asphalt emulsion. BoneDry TG is used as a below-grade exterior waterproofing compound and exhibits excellent strength, adhesion, and flexibility. BoneDry TG is a premium grade waterproofing compound used in commercial building construction for detailed applications.

BoneDry TG can be effectively used as a sealant or patch for tie holes, protrusions, penetrations, cold joints and honeycombs. This product is also a great choice for repairing cracks, seam failures and other water penetration points on existing structures. BoneDry TG is also used as an adhesive for flashing and other termination materials.

APPLICATIONS

- Masonry Foundations
- Poured Foundations
- Pre-Cast Foundations
- Horizontal

TECHNICAL DATA

Property	Testing	Value
Color		Black/Brown
Solids		63% ± 2%
Thickness		40-60 mil dry
Tensile Strength	ASTM D 412	87 psi
Elongation	ASTM D 412	1800%
MVT	ASTM E 96	0.19 gr/hr* sq. ft.
Adhesion to Concrete	ASTM C 834	Exceeds
Shore Hardness	ASTM C 836	75
Crack Bridging	ASTM C 836	Exceeds
Low Temp Flexibility	ASTM C 836	No Cracking
Perm Rating	ASTM C 836	0.38 perms

The information and recommendations discussed in this publication are believed to be correct. The ASTM testing is conducted by an independent accredited laboratory. No statement should be construed as a recommendation for any use, which would violate any patent rights. This document is not a guarantee of a warranty, if approved by GMX, Inc., a performance warranty may be granted.

