



1. PRODUCT NAME

Comfort Dry

2. MANUFACTURER

GMX, Inc.
3800 E. 91st Street
Cleveland, OH 44105
Phone: 866-228-7743

3. PRODUCT DESCRIPTION

Comfort Dry is a durable ready-to-use elastomeric waterproofing product that is made from pure acrylic resin. Comfort Dry will not peel, chip, blister or crack. It is used for both new construction and restoration. Comfort Dry is designed to waterproof concrete, masonry and other surfaces that will be exposed to the environment in above grade applications. Comfort Dry is washable and paintable.

4. PRODUCT ADVANTAGES

- Forms a thick rubber-like blanket of protection
- Protects against moisture
- 100% acrylic elastomeric resin for durability and long life
- Expands and contracts with surface material
- Retains flexibility from -30°F to 160°F
- High solids for better coverage
- Cured elastomeric film is mildew and algae resistant
- Has excellent accelerated weathering properties
- Soap and water cleanup - while wet

5. USES

Comfort Dry is suitable for application over painted and unpainted surfaces of cement, cinder block, concrete, brick, stone, stucco, tile, plaster and composition board.

6. APPLICATION

Do not attempt to paint over dirt, grease and loose or chalky mortar. Clean the surface as needed and repair loose or

chalky mortar as required. Comfort Dry is ready to use as is; however, some stirring may be necessary. Stir slowly (preferably with a paddle). It is not necessary to dampen the surface to be painted but slight surface dampness will not impede the bonding properties of Comfort Dry . DO NOT ATTEMPT TO COAT HEATED WALL SURFACES.

Comfort Dry can be applied by brush, spray, or roller. May need at least two coats to achieve the proper thickness of 25 sq. ft./gal. (60 mils wet; 40 mils dry), especially if using a brush or roller. DO NOT APPLY COMFORT DRY IF RAIN IS ANTICIPATED WITHIN 6 - 8 HOURS AFTER APPLICATION.

7. TECHNICAL SERVICES

Your local GMX representative is available to assist you in selecting the appropriate product and to provide on site application assistance. For further information, please contact our Technical Service Department at 866-228-7743.

NOTE: Packaged material cannot freeze. Keep in heated storage.

TECHNICAL DATA - Comfort Dry	
% Solids (ASTM D1644)	66%
VOC (ASTM 3960)	<50 g/l
Density	8.6 lbs./gal
Tensile Strength (ASTM D412)	>200 psi
Elongation (ASTM D412)	460%
Tear Resistance (ASTM 624)	60 lbsf/in
Weathering (ASTM D4798)	>1,000 hrs per ASTM G 26
Shelf Life	Less than 1 year unopened

7 FLUID APPLIED
Dampproofing Paint



© 2019 Garland Industries, Inc.

GMX, Inc.
3800 E. 91st Street
Cleveland, OH 44105
Toll Free: 866-228-7743
Fax: 704-334-4202
www.gmxwaterproofing.com