



# ULTRA-SHIELD MASONRY SEALER

## 1. PRODUCT NAME

**Ultra-Shield Masonry Sealer**

## 2. MANUFACTURER

GMX, Inc.  
3800 E. 91st Street  
Cleveland, OH 44105  
Phone: 866-228-7743  
Fax: 216-430-3500

## 3. PRODUCT DESCRIPTION

Ultra-Shield Masonry Sealer is a solvent-based, silicone solution designed to dampproof above grade masonry surfaces. Ultra-Shield Masonry Sealer is a transparent, colorless, thin liquid. It bars water from exterior masonry (above grade) surfaces without changing the texture of the surface over which it is applied.

## 3. PRODUCT ADVANTAGES

**Protects Masonry Surfaces** - Ultra-Shield Masonry Sealer penetrates masonry surfaces to keep water, dirt, and grime out of masonry pores. It protects mortar joints thereby minimizing damage caused by expansion and contraction. Ultra-Shield Masonry Sealer forms a water repellent surface which will last for years.

**Protects Interior Wall Surfaces** - Ultra-Shield Masonry Sealer eliminates moisture penetration from exterior, above grade masonry surfaces. It prevents peeling and flaking of interior finishes.

**Improve, Preserves Building Appearance** - Ultra-Shield Masonry Sealer is a clear, colorless liquid which does not change masonry appearance. It is self cleaning; dirt and grime wash off during rainstorms. Ultra-Shield Masonry Sealer minimizes masonry staining, flaking and temporary discoloration caused by absorbed moisture.

## 5. APPLICATION

All surfaces to be treated must be free of all dirt, excess mortar, loose particles and all foreign materials. Remove salt deposits from previous efflorescence by washing with diluted muriatic acid and flush with water. Grease and oil stains must be removed using high strength detergents or cleaning solvents. Rinse with water. Repoint all joints with loose mortar or where mortar is missing. Repair all hair line cracks or larger cracks and holes. Allow new masonry walls to cure at least 2 to 3 weeks before applying Ultra-Shield Masonry Sealer.

Apply Ultra-Shield Masonry Sealer with a wide brush or spray until the surface appears shining wet. When using a brush for application, dab or splash the material on. Ultra-Shield Masonry Sealer is a thin coating and does not brush out like paint. When spraying, use a nozzle with a coarse, round tip to obtain a generous rather than a fine, misty spray.

## 6. QUALITY AND CONSISTENCY - ISO 9001

Ultra-Shield Masonry Sealer is manufactured to the highest quality standards and in accordance with ISO 9001 requirements. ISO certification ensures that every gallon manufactured meets the highest quality control standards in the industry and provides outstanding performance in the field.

## 7. TECHNICAL SERVICES

Your local GMX representative is available to assist you in selecting the appropriate product and to provide on-site application assistance. For further information, please contact our Technical Service Dept. at 866-228-7743.

TECHNICAL DATA - Ultra-Shield Masonry Sealer	
Density @ 77°F (25°C)	6.7 lbs. per gal (0.80 g/cm <sup>3</sup> )
Carrier	Solvent Mineral Spirits
Flash Point (ASTM D 93)	105°F (40°C)
Coverage depending on porosity	75-200 ft <sup>2</sup> /gal (1.84-4.91 m <sup>2</sup> /l)
Packaging	5 gal. pail (18.9 l)

**7**  
**FLUID APPLIED**  
Dampproofing Sealer



© 2013 Garland Industries, Inc.

GMX, Inc.  
3800 E. 91st Street  
Cleveland, OH 44105  
Toll Free: 866-228-7743  
Fax: 216-430-3500  
www.gmxwaterproofing.com